RECESSED DOWNLIGHTS

NEBULA TRIO



Description:

Nebula TRIO LED downlights are ideal ceiling-mounted fixtures that provide bright, energy-efficient illumination. They are designed to meet all your indoor lighting needs, they feature long lifespan and high performance, making them the perfect choice for homes and offices.



Specifications:


Wattage	Lumen	Efficacy	Power Factor	CRI	ССТ	Voltage	Frequency	Dimensions (mm)				
								L	W	Cut-out	H IP20 IP65	
18W	1620lm	90lm/w	>0.95	≥80	2700-5700K	220-240 VAC	50/60 Hz	232	85	224x75	112	121
30W	2700lm	90lm/w	>0.95	≥80	2700-5700K	220-240 VAC	50/60 Hz	232	85	224x75	112	121
42W	3780lm	90lm/w	>0.95	≥80	2700-5700K	220-240 VAC	50/60 Hz	232	85	224x75	112	121
60W	5400lm	90lm/w	>0.95	≥80	2700-5700K	220-240 VAC	50/60 Hz	292	105	284x95	138	146

^{*}Available in other CCTs on request.


Features:

Body Material	Finishing	Optics	Driver	Driver Mounting	Beam Angle	
Die-Cast Aluminum	Electrostatic Painting	PMMA Lens with Outer PC Reflector	Included	Separated - Outside	15°, 36° & 60°	

Photometric:



General Dimensions:



Reflector Finish:



Applications:















^{*}Available in CRI 90 on request.
*Above values are based on SEI calibrated machines testing on the white matt reflector.