
# **RECESSED DOWNLIGHTS**

# **NEBULA OVAL TLR**



### **Description:**

Nebula Pop-out Oval TLR **trimless**, retractable downlights offer exceptional flexibility for residential and retail lighting. They provide precise, focused illumination to highlight interior details. Their retractable structure allows for seamless integration into modern interiors, enabling dynamic lighting adjustments.











### **Specifications:**


Wattage	Lumen	Efficacy	Power Factor	CRI	ССТ	Voltage	Frequency	Dimensions (mm)			
								L	W	Cut-out	Н
12W	1140lm	95lm/w	>0.95	≥ 80	2700-5700K	220-240 VAC	50/60 Hz	177	88	179x91	116
20W	1900lm	95lm/w	>0.95	≥ 80	2700-5700K	220-240 VAC	50/60 Hz	177	88	179x91	116
28W	2660lm	95lm/w	>0.95	≥ 80	2700-5700K	220-240 VAC	50/60 Hz	177	88	179x91	116
40W	3800lm	95lm/w	>0.95	≥80	2700-5700K	220-240 VAC	50/60 Hz	222	108	224x111	140

<sup>\*</sup>Available in other CCTs on request.


#### **Features:**

Body Material	Finishing	Optics	Driver	Driver Mounting	Beam Angle
Die-Cast Aluminum	Electrostatic Painting	PMMA Lens with Outer PC Reflector	Included	Separated - Outside	15°, 36° & 60°

#### **Photometric:**



### **General Dimensions:**



### **Reflector Finish:**



# **Applications:**















<sup>\*</sup>Available in CRI 90 on request.

<sup>\*</sup>Above values are based on SEI calibrated machines testing while using wide beam angles & on the black matt reflector.